

## LIGHT LIQUID SEPARATOR ECODEPUR<sup>®</sup> TECHNOIL<sup>®</sup> NS50

## TECHNICAL INFORMATION


ECODEPUR<sup>®</sup> TECHNOIL<sup>®</sup> is Light Liquid Separator destined to clean water polluted with light free floating liquids such as engine oils, gas, oil etc, Class 1 in according of EN 858, with double coalescent cell and automatic closure device.



ECODEPUR<sup>®</sup> TECHNOIL<sup>®</sup> Separators has CE marking, in accordance with the legal obligations that stems from the entry into force of the Regulation (UE) N.º 305/2011 of Construction Products, fulfilling all the requisites of the European Standard EN 858-1:2002.

<b>EUROPEAN STANDARD</b>	EN 858-1
<b>EQUIPMENT IDENTIFICATION</b>	Light Liquid Separator
<b>MARCA</b>	ECODEPUR <sup>®</sup>
<b>TYPE</b>	TECHNOIL <sup>®</sup> NS50
<b>CLASS EN 858-1</b>	Class 1 (<5,0 mg "Mineral Oils"/l <sup>(1)</sup> )
<b>NOMINAL SIZE</b>	50 l/s
<b>COALESCENT CELL</b>	Lamellar
<b>AUTOMATIC CLOSURE DEVICE</b>	Included (system always calibrated)
<b>VOLUME PRE-SLUDGE TRAP</b>	5.000 l
<b>OIL STORAGE</b>	5.000 l
<b>FIRE CLASS REACTION</b>	F
<b>MATERIAL</b>	Polyethylene
<b>VENTE POINT</b>	Included (1 1/2")
<b>COVER</b>	Polyethylene

<sup>(1)</sup> Teste conditions EN 858-1



TYPE	NS (l/s)	VOLUME (l)	Ø (mm)	L (mm)	H (mm)	He (mm)	Hs (mm)	C (mm)	Ø PIPE (mm)	WEIGHT (kg)
TECHNOIL <sup>®</sup> NS50	50	10.000	2.190	3.440	2.265	1.685	1.585	790	315	580

Rev.1\_02.03.16 | The pictures and dimensions can be changed without notice.